10-10-00

A

Please type a plus sign (+) inside this box → +

PTO/SB/05 (08-00)
Approved for use through 10/31/2002. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.	1204US
First Inventor	David Drell
Title	Videoconferencing Apparatus
Express Mail Label No.	EL666126127US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Box Patent Application, Washington, DC 20231

1. [X] Fee Transmittal Form (e.g., PTO/SB/17) *(Submit an original and a duplicate for fee processing)*
2. [ ] Applicant claims small entity status. See 37 CFR 1.27.
3. [X] Specification [*Total Pages* 26] *(preferred arrangement set forth below)*
   - Descriptive title of the invention
   - Cross Reference to Related Applications
   - Statement Regarding Fed sponsored R & D
   - Reference to sequence listing, a table, or a computer program listing appendix
   - Background of the Invention
   - Brief Summary of the Invention
   - Brief Description of the Drawings *(if filed)*
   - Detailed Description
   - Claim(s)
   - Abstract of the Disclosure
4. [X] Drawing(s) *(35 U.S.C. 113)* [*Total Sheets* 5]
5. Oath or Declaration [*Total Pages*]
   - a. [ ] Newly executed (original or copy)
   - b. [ ] Copy from a prior application (37 CFR 1.63 (d)) *(for continuation/divisional with Box 17 completed)*
     - i. [ ] DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
6. [ ] Application Data Sheet. See 37 CFR 1.76
7. [ ] CD-ROM or CD-R in duplicate, large table or Computer Program *(Appendix)*
8. Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all necessary)*
   - a. [ ] Computer Readable Form (CRF)
   - b. Specification Sequence Listing on:
     - i. [ ] CD-ROM or CD-R (2 copies); or
     - ii. [ ] paper
   - c. [ ] Statements verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

9. [ ] Assignment Papers (cover sheet & document(s))
10. [ ] 37 CFR 3.73(b) Statement *(when there is an assignee)* [ ] Power of Attorney
11. [ ] English Translation Document *(if applicable)*
12. [ ] Information Disclosure Statement (IDS)/PTO-1449 [ ] Copies of IDS Citations
13. [ ] Preliminary Amendment
14. [X] Return Receipt Postcard (MPEP 503) *(Should be specifically itemized)*
15. [ ] Certified Copy of Priority Document(s) *(if foreign priority is claimed)*
16. [ ] Other: .....

17. If a CONTINUING APPLICATION, *check appropriate box, and supply the requisite information below and in a preliminary amendment, or in an Application Data Sheet under 37 CFR 1.76:*

[ ] Continuation [ ] Divisional [ ] Continuation-in-part (CIP) of prior application No.: _____ / _____

Prior application information. Examiner _____ *Group / Art Unit.* _____

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

18. CORRESPONDENCE ADDRESS

[ ] *Customer Number or Bar Code Label* *(Insert Customer No. or Attach bar code label here)* or [ ] *Correspondence address below*

Name	22830 PATENT TRADEMARK OFFICE				
Address					
City		*State*		*Zip Code*	
Country		*Telephone*		*Fax*	

Name (Print/Type)	Douglas E. Mackenzie	*Registration No. (Attorney/Agent)*	38,955
Signature	Douglas E. Mackenzie	*Date*	10/5/2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

PTO/SB/17 (08-00)
Approved for use through 10/31/2002. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL for FY 2000

Patent fees are subject to annual revision.

TOTAL AMOUNT OF PAYMENT ($) 710.00

Complete if Known	
Application Number	unknown
Filing Date	10/5/2000
First Named Inventor	David Drell
Examiner Name	
Group Art Unit	
Attorney Docket No.	1204US

METHOD OF PAYMENT (check one)

1. [X] The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to:
   - Deposit Account Number: 06-0600
   - Deposit Account Name:
   - [X] Charge Any Additional Fee Required Under 37 CFR 1.16 and 1.17
   - [ ] Applicant claims small entity status. See 37 CFR 1.27
2. [X] **Payment Enclosed:** [X] Check [ ] Credit card [ ] Money Order [ ] Other

FEE CALCULATION

1. BASIC FILING FEE

Large Entity Fee Code	Large Entity Fee ($)	Small Entity Fee Code	Small Entity Fee ($)	Fee Description	Fee Paid
101	690	201	345	Utility filing fee	710.00
106	310	206	155	Design filing fee	
107	480	207	240	Plant filing fee	
108	690	208	345	Reissue filing fee	
114	150	214	75	Provisional filing fee	

SUBTOTAL (1) ($) 710.00

2. EXTRA CLAIM FEES

		Extra Claims		Fee from below	Fee Paid
Total Claims	12	-20** =		X	=
Independent Claims	2	- 3** =		X	=
Multiple Dependent					=

**or number previously paid, if greater; For Reissues, see below

Large Entity Fee Code	Large Entity Fee ($)	Small Entity Fee Code	Small Entity Fee ($)	Fee Description
103	18	203	9	Claims in excess of 20
102	78	202	39	Independent claims in excess of 3
104	260	204	130	Multiple dependent claim, if not paid
109	78	209	39	** Reissue independent claims over original patent
110	18	210	9	** Reissue claims in excess of 20 and over original patent

SUBTOTAL (2) ($)

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Large Entity Fee Code	Large Entity Fee ($)	Small Entity Fee Code	Small Entity Fee ($)	Fee Description	Fee Paid
105	130	205	65	Surcharge - late filing fee or oath	
127	50	227	25	Surcharge - late provisional filing fee or cover sheet	
139	130	139	130	Non-English specification	
147	2,520	147	2,520	For filing a request for *ex parte* reexamination	
112	920*	112	920*	Requesting publication of SIR prior to Examiner action	
113	1,840*	113	1,840*	Requesting publication of SIR after Examiner action	
115	110	215	55	Extension for reply within first month	
116	380	216	190	Extension for reply within second month	
117	870	217	435	Extension for reply within third month	
118	1,360	218	680	Extension for reply within fourth month	
128	1,850	228	925	Extension for reply within fifth month	
119	300	219	150	Notice of Appeal	
120	300	220	150	Filing a brief in support of an appeal	
121	260	221	130	Request for oral hearing	
138	1,510	138	1,510	Petition to institute a public use proceeding	
140	110	240	55	Petition to revive - unavoidable	
141	1,210	241	605	Petition to revive - unintentional	
142	1,210	242	605	Utility issue fee (or reissue)	
143	430	243	215	Design issue fee	
144	580	244	290	Plant issue fee	
122	130	122	130	Petitions to the Commissioner	
123	50	123	50	Petitions related to provisional applications	
126	240	126	240	Submission of Information Disclosure Stmt	
581	40	581	40	Recording each patent assignment per property (times number of properties)	
146	690	246	345	Filing a submission after final rejection (37 CFR § 1.129(a))	
149	690	249	345	For each additional invention to be examined (37 CFR § 1.129(b))	
179	690	279	345	Request for Continued Examination (RCE)	
169	900	169	900	Request for expedited examination of a design application	

Other fee (specify) _____

* Reduced by Basic Filing Fee Paid

SUBTOTAL (3) ($)

SUBMITTED BY

Complete *(if applicable)*

Name (Print/Type)	Douglas E. Mackenzie	Registration No (Attorney/Agent)	38,955	Telephone	650-812-3400
Signature	Douglas E. Mackenzie			Date	10/5/2000

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Burden Hour Statement. This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS SEND TO: Assistant Commissioner for *Patents, Washington, DC* 20231.

VIDEOCONFERENCING APPARATUS HAVING INTEGRATED MULTI-POINT CONFERENCE CAPABILITIES

Cross Reference to Related Applications

The present invention claims priority from U.S. Provisional Patent Application Ser. No. 60/157,711 filed on October 5, 1999, the entire disclosure of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to conferencing systems, and more particularly to a videoconferencing apparatus for use with multi-point conferences.

2. Background of the Prior Art

Videoconferencing systems have become an increasingly popular and valuable business communications tool. These systems facilitate rich and natural communication between persons or groups of persons located remotely from each other, and reduce the need for expensive and time-consuming business travel.

At times, it may be desirable to conduct multi-point conferences, wherein three or more parties (each party consisting of an individual or group located at a particular conference endpoint) participate in the conference. Multi-point conferences are particularly useful in situations where several interested parties need to participate in the resolution of an issue, or where information is to be disseminated on an enterprise-wide level. However, commercially available video conferencing systems are generally capable of communicating with only one other conference endpoint at a time. To conduct multi-point conferences, the conference endpoints are conventionally interconnected through an external piece of equipment called a multi-point control unit (MCU). The MCU is provided with multiple ports for receiving signals representative of audio and video information generated at each of the conference endpoints. The received signals are mixed and/or switched as appropriate, and the mixed/switched signals are subsequently transmitted to each of the conference endpoints.

A significant disadvantage associated with the use of MCUs is their expense. An enterprise wishing to conduct multi-point conferences must either purchase a MCU, which may cost upwards of $50,000, or contract for "video bridge"

services through a telephone company, wherein an MCU located at the telephone company's facilities is rented on a fee per unit of usage basis. In either case, the high cost of purchasing or renting an MCU may dissuade a company from conducting multi-point conferences, even when it would be useful to do so.

Conventional MCUs further require a dedicated Inverse Multiplexer (IMUX) for each endpoint of a multi-point conference. These dedicated IMUXs are hardware devices which must be purchased and installed at additional cost to achieve increased endpoint capability.

Finally, conventional MCUs include hard-wired processing units each having a dedicated set of channels associated therewith. Thus, unused channels associated with a processing unit are unavailable for allocation to additional endpoints.

What is therefore needed in the art is a relatively low-cost videoconferencing apparatus which can dynamically allocate unused channels on an as needed basis.

SUMMARY OF THE INVENTION

The present invention is directed to a multi-point (MP) conferencing application having dynamically allocable software-based IMUX functions. The IMUX functions are implemented in a software-based circuit switch operable to aggregate a plurality of processing trains to a wideband serial data stream. The IMUX functions are created on an as needed basis for each endpoint in a multi-point conference.

The MP conferencing application is coupled to a conventional network interface including a time division multiplexer. The time division multiplexer is in turn coupled to a plurality of communication ports, which may typically include ISDN ports, enabling an apparatus including the MP conferencing application to be coupled to two or more remote conference endpoints through a switched network.

The (MP) conferencing application is operable to process the plural signal streams received through the communication ports. Generally, the MP conferencing application generates separate processing trains for signal streams from/to each of the remote conference endpoints. The processing trains each comprise a communication process and a set of codecs. In the receive mode, an IMUX function

combines signal streams (representative of a single conference endpoint) distributed over two or more channels into a single, relatively high bandwidth channel. The communication process, which may for example comprise an H.320 process (ISDN-based) or H.323 (packet-based) process, separates the signal stream into audio and video signals, and performs certain processing operations (such as delay compensation) associated therewith. The audio and video signals are thereafter respectively delivered to audio and video codecs for decoding.

The decoded audio and video streams output by each of the processing trains, together with the locally generated audio and video signals, are combined at an audio mixer and a video switching/continuous presence module. The video module may be configured to selectively generate as output video data representative of a composite or continuous presence image, wherein video information (e.g., images of the conference participants) corresponding to each of the conference endpoints is displayed in different sectors of the screen. The combined audio and video data streams are conveyed as input to each processing train for encoding and transmission to the corresponding conference endpoints. In the send mode, the audio and video signals are encoded by the audio/video codecs and multiplexed into a single data

stream by the communication process. The combined audio/video data stream is then conveyed to the IMUX function, which distributes the combined audio/video data stream over the channels associated with the selected remote conference endpoint.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 depicts a near videoconferencing endpoint interconnected with two remote videoconferencing endpoints, the near videoconferencing endpoint having integrated multi-point conferencing capabilities;

FIG. 2 is a block diagram of the near conferencing endpoint;

FIG. 3 is a block diagram of a multi-point conferencing application of FIG. 2;

FIG. 4 is a block diagram of an exemplary signal processing train of FIG. 3; and

FIG. 5 is a block diagram of an exemplary network interface.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

FIG. 1 depicts an exemplary operating environment of the multi-point (MP) conferencing application of the present invention. A near conference endpoint 100, embodying the MP conferencing application, is coupled to remote conference endpoints 102 and 104 via a network 106. Remote conference endpoints 102 and 104 may comprise, for example, conventional videoconferencing devices equipped to transmit and receive both video (image) data and audio (speech) data. Alternatively, one or more of remote conference endpoints 102 and 104 may comprise conventional audio conferencing devices limited to reception and transmission of audio data. It should be appreciated that while only two remote conference endpoints are depicted in FIG.1 for the purpose of clarity, a greater number of remote conference endpoints may be accommodated by near conference endpoint 100.

Network 106 may be of any type suitable for the transmission of audio and video data between and among near conference endpoint 100 and remote conference endpoints 102 and 104. Typically, network 106 will comprise the public switched telephone network (PSTN) or comparable circuit switched network to which each of the conference endpoints is connected by one or more ISDN lines. A multi-point

conference is initiated by establishing a connection between near conference endpoint 100 and remote conference endpoint 102, and between near conference endpoint 100 and remote conference endpoint 104. Establishment of the connections may be effected through a dial-up procedure, or through use of a dedicated line.

Alternatively, network 106 may comprise a packet switched network, such as the Internet. Although a single network 106 is shown, the invention contemplates the use of two or more networks (for example, the PSTN and the Internet) to connect conference endpoints utilizing different communication protocols.

Reference is now directed to FIG. 2, which depicts in block form various components of near conference endpoint 100. A conventional video camera 202 and microphone 204 are operative to generate video and audio signals representative of the images and speech of the near conference participant (the person or persons co-located with near videoconference endpoint 100). A video monitor 208 and loudspeaker 210 present images and speech of the remote conference participants combined with locally generated images and speech. An audio I/O interface 212, configured to perform A/D and D/A conversion and related processing of audio signals, couples microphone 204 and

loudspeaker 210 to CPU 220 and memory 222 through bus 226. Similarly, video camera 202 and monitor 208 are coupled to console electronics 213 through video I/O interface 214.

Console electronics 213 additionally include a central processing unit (CPU) 220 for executing program instructions, a memory 222 for storing applications, data, and other information, and a network interface 224 for connecting near conference endpoint 100 to network 106. Memory 222 may variously comprise one or a combination of volatile or non-volatile memories, such as random access memory (RAM), read-only memory (ROM), programmable ROM (PROM), or non-volatile storage media such as hard disks or CD-ROMs. At least one bus 226 interconnects the components of console electronics 213.

Network interface 224 is provided with a plurality of ports for physically coupling near conference endpoint 100 to a corresponding plurality of ISDN lines 240-246 or similar transmission media. The number of ports will be determined by the types of connections to network 106, the maximum number of remote conference endpoints which may be accommodated by videoconference endpoint 100, and the required or desired bandwidth per endpoint connection. Depending on bandwidth requirements, data communicated between near conference endpoint 100 and a remote

conference endpoint may be carried on a single ISDN line, or may be distributed (for higher bandwidth connections) among a plurality of ISDN lines.

Stored within memory 222 are an operating system 230, a call manager application 232, and the MP conferencing application 234. Operating system 230 controls the allocation and usage of hardware resources, such as CPU 220 and memory 222. Call manager application 232 controls the establishment and termination of connections between near conferencing endpoint 100 and remote conference endpoints 102 and 104, and may also furnish information characterizing the nature of individual connections to MP conferencing application 234.

As will be described in further detail below, MP conferencing application 234 is configured to instantiate a processing train for each remote conference endpoint 102 and 104 to which near conference endpoint 100 is connected. The processing trains process audio and video data streams received from remote conferencing endpoints 102 and 104. The processed audio and video data streams are combined with each other and with locally generated audio and video streams, and the combined audio and video streams are thereafter distributed to remote conferencing endpoints 102 and 104.

FIG. 3 is a block diagram showing the various components of an embodiment of MP conferencing application 234 and the flow of data between and among the various components. MP conferencing application 234 includes a circuit switch 350, a plurality of processing trains 302 and 304, a video switching/continuous presence module 306, and an audio mixing module 308. The circuit switch 350 dynamically instantiates a number of high bandwidth processing trains equal to the number of remote conference endpoints to which near conference endpoint 100 is connected and preferably includes an dynamically created IMUX allocated to each remote conference endpoint. Each IMUX preferably utilizes a bonding protocol. In the example depicted in the figures, the circuit switch 350 dynamically allocates two IMUXs and generates two processing trains 302 and 304 respectively corresponding to remote conference endpoints 102 and 104.

Processing trains 302 and 304 preferably comprise software routines which process received and transmitted audio and video signals in accordance with predetermined algorithms. In the receive mode, processing train 302 is instantiated by circuit switch 350 to include signals representative of audio and video data transmitted by remote conference endpoint 102. Illustratively, remote

conference endpoint 102 may transmit signals on ISDN lines, each ISDN line comprising two distinct 64 Kb/sec bi-directional channels ("Bearer channels"). Those skilled in the art will recognize that a smaller or greater number of ISDN lines may be utilized for communication with remote conference endpoint 102. As will be described in connection with FIG. 4, processing train 302 is operative to extract and decode audio and video data from signals received from remote conference endpoint 102. Decoded audio data is conveyed to audio mixing module 308 over audio data path 352, and decoded video data is conveyed to video switching/continuous presence module 306 over video data path 354.

Processing train 304 similarly receives audio and video data transmitted by remote conference endpoint 104. Processing train 304 extracts and decodes the audio and video data and subsequently passes the decoded audio and video data to audio mixing module 308 and video switching/continuous presence module 306 over audio and video data paths 370 and 372.

Audio mixing module 308 is configured to combine audio data received from remote conference endpoints 102 and 104 with locally generated audio data (received from audio I/O interface 212 via audio data path 374, and typically being

representative of the speech of the near conference participant(s)). The term "combine" is used in its broadest and most general sense and is intended to cover any operation wherein audio mixing module 308 generates an output audio data stream (or plurality of output audio data streams) based on information contained in the remotely and locally generated audio data input streams. For example, audio mixing module 308 may simply mix the received audio input data streams, or it may be configured as an audio switch wherein it selects one of the received audio input data streams for output in accordance with predetermined criteria. The output audio data stream is directed to processing trains 302 and 304 and audio I/O interface 212 along output audio paths 376, 378 and 380.

Video switching/continuous presence module 306 combines video data received from remote conference endpoints 102 and 104 with locally generated video data (received from video I/O interface 214 via video data path 382, and being typically representative of images of the near conference participants). Again, the term "combine" is used in its broadest and most general sense. In one mode of operation, video switching/continuous presence module 306 may select one of the video data input streams for output based on predetermined criteria (for example, it

may select for output the video data stream corresponding to the conference endpoint of the currently speaking participants. In a second mode of operation (referred to as the "continuous presence mode"), video switching/continuous presence module 306 may construct a composite image wherein images corresponding to conference endpoints are displayed in different sectors of the composite image. The video data stream output (or plurality of outputs) from video switching continuous presence module 306 is thereafter distributed to processing trains 302 and 304 and video I/O interface 214 via video data paths 390, 392 and 394.

In the transmission mode, processing train 302 is configured to receive the audio and video data streams output by audio mixing module 308 and video switching/continuous presence module 306. The received data streams are then encoded and combined to form a mixed encoded audio/video data stream, and the encoded audio/video data stream is transmitted to the circuit switch 350 via data path 344. Similarly, processing train 304 receives the audio and video streams output by audio mixing module 308 and video switching/continuous presence module 306, encodes and combines the audio and video data streams, and transmits the encoded audio/video data stream

to the circuit switch 350 via data path 346. For each encoded audio/video data stream, the circuit switch 350 allocates an IMUX which aggregates the data streams into a wideband data stream on the bus 226, preferably utilizing a bonding protocol.

FIG. 4 depicts components of an exemplary processing train 302. Processing train 302 includes a communication process 404 and video and audio codecs 406 and 408. In the receive mode, the combined data stream 344 is directed to communication process 404 which carries out a predetermined set of functions with respect to data stream 344.

According to one embodiment of the invention, communication process 404 implements the multiplexing, delay compensation and signaling functions set forth in ITU Recommendation H.320 ("Narrow-Band Visual Telephone Systems and Terminal Equipment"). In particular, communication process 404 includes a multiplexer/demultiplexer for (in the receive mode) extracting separate audio and video signals from mixed data stream 344 in accordance with ITU Recommendation H.221. Communication process 404 may further include a delay compensation process for inducing a delay in the audio data path in order to maintain lip synchronization. A system control unit is incorporated into communication process 404 and is configured to

establish a common mode of operation with remote conference endpoint 102 in accordance with ITU Recommendation H.242.

Audio codec 408 receives the audio data stream from communication process 404 and applies redundancy reduction decoding in accordance with a standard (e.g., ITU Recommendation G.711) or proprietary audio compression algorithm. The decoded audio data stream is then sent to audio mixing module 308, as described above. Similarly, video codec 406 receives the video data stream and applies redundancy reduction decoding in accordance with a standard (e.g., ITU Recommendation H.261) or proprietary video compression algorithm. The decoded video data stream is subsequently sent to video switching/continuous presence module 306 for combination with video data generated by remote conference endpoint 104 and near conference endpoint 100, as described above in connection with FIG. 3.

In the transmit mode, video codec 406 encodes the video data stream output by video switching/continuous presence module 306 (representative, for example, of a "continuous presence" image) using a standard or proprietary video compression algorithm (e.g., H.261) and delivers the encoded video data to communication process 404. Audio codec 408 encodes the audio data stream output by audio mixing module 308 (representative, for example, of

the blended speech of conference participants located at near conference endpoint 100 and remote conference endpoints 102 and 104) using a standard or proprietary audio compression algorithm (e.g., G.711) and delivers the encoded audio data to communication process 404.

Communication process 404 multiplexes the encoded audio and video data streams into a single audio/video data stream 344 of relatively high bandwidth. The audio/video data stream is conveyed to circuit switch 350, which breaks up and distributes the high-bandwidth audio/video data signal over plural ISDN channels as further described hereinbelow.

It is noted that, while not depicted in the Figures, processing train 302 may include a data codec for coding and encoding still images and the like received from or transmitted to remote conference endpoints 102 and 104.

With reference to FIG. 5 the network interface 224 includes a time division multiplexer 502 which receives the wideband data stream 226 from the circuit switch 350. The time division multiplexer 502 is coupled to a plurality of ISDN ports 504 for receiving and transmitting signals on lines 240, 242, 244, and 246.

The present invention advantageously utilizes software-based processing of video and audio data streams

to implement a multi-point conferencing capability in a conference endpoint. By dynamically generating a separate instance of a processing train for each remote endpoint session, a videoconferencing system embodying the invention may easily and flexibly accommodate endpoint sessions comprising a range of connection bandwidths and communication protocols. Other advantages will occur to those of ordinary skill upon review of the foregoing description and the associated figures.

It is to be understood that the detailed description set forth above is provided by way of example only. Various details of design, implementation or mode of operation may be modified without departing from the true spirit and scope of the invention, which is not limited to the preferred embodiments discussed in the description, but instead is set forth in the following claims.

CLAIMS

What is claimed is:

1. A multi-point conferencing apparatus for conducting a conference with a plurality of remote conference endpoints linked for communication by a network, the apparatus comprising:

a multi-point conference application for receiving audio and video signals from the plurality of remote conference endpoints, processing the received audio and video signals, combining the processed audio and video signals with the local audio and video signals, and transmitting the combined audio and video signals to each of the plurality of remote conference endpoints, the multi-point conference application being configured to create a plurality of processing trains corresponding to the plurality of remote conference endpoints, each processing train processing audio and video signals from a selected one of the remote conference endpoints.

2. The apparatus of claim 1, wherein the multi-point conference application comprises a circuit switch for instantiating the plurality of processing trains, the circuit switch including dynamically allocable inverse multiplexers.

3. The apparatus of claim 1, wherein the multi-point conference application includes a video switching module for combining the remote and local video signals, and an audio mixer for combining the remote and local audio signals, the video switching module and audio mixer directing the combined signals as input to each of the processing trains.

4. The apparatus of claim 3, wherein the video switching module is selectively operable in a continuous presence mode, wherein images corresponding to each of the plurality of conference endpoints are displayed in separate areas of a composite image.

5. The apparatus of claim 1, further comprising a plurality of ISDN ports, each coupleable to an ISDN line, for receiving and transmitting audio and video signals from and to the conference endpoints over the network, each conference endpoint having at least one of the plurality of ISDN ports corresponding thereto.

6. The apparatus of claim 1, wherein each of the plurality of processing trains comprises a communication process and a set of codecs.

7. The apparatus of claim 6, wherein the communication process comprises an H.320 communication process.

8. A method for conducting a conference between a near conference endpoint and a plurality of remote conference endpoints connected for communication by a network, comprising the steps of:

at the near conference endpoint:

generating local audio and video signals;

receiving audio and video signals from the plurality of remote conference endpoints;

creating a plurality of processing trains for processing the received signals, each processing train uniquely corresponding to one of the plurality of remote conference endpoints;

processing the received audio and video signals;

combining the processed audio and video signals with the local audio and video signals; and

transmitting the combined audio and video signals to each of the plurality of remote conference endpoints.

9. The method of claim 8, wherein the step of creating a plurality of processing trains includes creating a communication process and a set of codecs.

10. The method of claim 8, wherein the step of combining the processed audio and video signals is performed using an audio mixer and a video switching module.

11. The method of claim 8 further comprising providing a circuit switch for instantiating the plurality of processing trains, the circuit switch including dynamically allocable inverse multiplexers.

12. The method of claim 10, wherein the video switching module is selectively operable in a continuous presence mode, wherein images corresponding to each of the plurality of conference endpoints are displayed in separate areas of a composite image.

ABSTRACT OF THE DISCLOSURE

A videoconferencing apparatus includes a multi-point (MP) conference application that enables the apparatus to combine and distribute audio and video signals received from a plurality of remote conference endpoints, thereby obviating the need to provide a separate multi-point control unit (MCU) having hardware-based inverse multiplexers (IMUXs). The videoconferencing apparatus has a plurality of communication ports (typically ISDN ports) for coupling the videoconferencing apparatus to the remote endpoints through a switched network. The MP conference application is configured to generate, for each remote conference endpoint participating in a conference, discrete instances of a signal processing train by means of dynamically allocable IMUXs, each processing train including a communication process (including multiplexing/demultiplexing and signaling functions) and audio/video/data codecs. Signals received at the communication ports are directed to the appropriate signal processing train for separate processing of each endpoint session. The processed audio and video signals are subsequently conveyed to an audio mixer and video switching module for combination with locally-generated audio and

video signals. The outputs of the audio mixer and video switching module are sent to each of the plurality of signal processing trains, which process the combined signals according to a transmit mode for distribution to the remote endpoints over the switched network.


100
NEAR CONFERENCE ENDPOINT A
104
REMOTE CONFERENCE ENDPOINT C
106
NETWORK
102
REMOTE CONFERENCE ENDPOINT B

FIG. 1


MICROPHONES
204
SPEAKERS
210
CAMERA(S)
202
MONITOR
208
AUDIO I/O INTERFACE
212
CPU
220
VIDEO I/O INTERFACE
214
213
NETWORK INTERFACE
224
226
232
CALL MANAGER
234
MP CONFERENCING
222
230
O/S
MEMORY
240
242
244
246
NEAR CONFERENCE ENDPOINT A
100
ISDN LINES

FIG. 2


306
390
302
344
350
354
382
214
Video Switching/
Continuous
Presence Module
Session B Processing
Train
Video I/O
Interface
352
376
392
226
Circuit
Switch
394
380
372
304
Audio I/O
Interface
Audio Mixing
Module
Session C Processing
Train
212
374
378
370
346
308
MP Conferencing Application
234

FIG. 3


302
406
404
From Video Switch
306
To Video Switch
306
Video Codec
Communication
Process
344
From Audio Mixer
308
To Audio Mixer
308
Audio Codec
408
Processing Train

FIG. 4


224
504
240
ISDN Port
502
242
ISDN Port
Time Division
Multiplexer
244
ISDN Port
226
246
ISDN Port
Network Interface

FIG. 5